

# HIGH PERFORMANCE INDUSTRIAL LUBRICANTS

From Press-Form Machinery Ltd  
in partnership with  
ACMA OLEOSYNTHESE

## DATA SHEET

### COMPOUNOIL SC18

## HIGH PERFORMANCE VANISHING LUBRICANT

### DESCRIPTION

A Chlorine free high performance vanishing lubricant with extreme pressure and anti-wear properties

### PROPERTIES

- Non chlorinated evaporative lubricant, free from aromatic hydrocarbons
- Excellent anti-wear and lubricating properties
- Excellent extreme pressure properties
- Practically odourless, excellent operator acceptability
- Fast evaporation
- After drying, residual film is easy to remove
- Parts can be de-greased easily with solvent or alkaline solutions

### FEATURES

	Unit	Value
Physical state	-	Liquid
Colour	-	Yellow
Density at 20°C (ISO 12185)	kg/m <sup>3</sup>	780
Flash point (ISO 2719)	°C	> 45
Kinematic viscosity at 40°C (ISO 3104)	mm <sup>2</sup> /s	1.8

### APPLICATIONS

- Blanking, bending and forming of sheet metal when post production cleaning is to be avoided
- Highly recommended for use on electroplated, galvanized, pre-painted or anodized sheet metal
- Heavy blanking or stamping of all steel types
- Can be applied directly by spraying, dipping, brushing or roller coating methods
- Not recommended for copper alloys due to a possibility of staining and dis-colouration

### Available Sizes:

Drums 60L, Barrel 210L Bulk Tank 1000L

